

**PRODUCT INFORMATION**

1191 Wheeling Road, Wheeling, IL 60090  
 Phone: 847-541-9000 Fax: 847-541-7549



**PRODUCT: 16458 Series**

**DESCRIPTION:**

Valspar® Elan™ Kitchen & Bath Mid-Sheen

**FEATURES:**

Valspar® Elan™ Kitchen & Bath is a revolutionary low-odor paint, which delivers enduring beauty in one lustrous coat. This 100% acrylic latex enamel utilizes the latest engineered ceramic technology that is extremely easy to apply without spattering. Elan contains an antimicrobial agent to prevent microorganisms from degrading the product. It is ideal for use in high humidity, frequently scrubbed and washed areas. Elan produces an elegant, long lasting finish.

**WHERE TO USE:**

Properly prepared interior wall, trim and ceiling surfaces including previously painted and primed plaster, wood, brick, drywall, cement and metal.

**SURFACE PREPARATION:**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces. Prime new wallboard with latex wall primer. Prime new wood with enamel undercoater or latex wall primer.

**16458 Series Valspar Elan Kitchen & Bath Mid-Sheen**

**TYPICAL PRODUCT PROPERTIES:  
(16458)**

VEHICLE TYPE: Acrylic Polymer  
 SOLIDS: 47% WT. 37% VOL.  
 VOC: 50 g/l max  
 WT/GAL: 10.0 lbs.  
 VISCOSITY: 96–104 KU  
 FLASHPOINT: N/A  
 60° GLOSS: 30–40 Units

**COVERAGE/THINNING:**

Covers up to 400 sq. ft. (37.2 m<sup>2</sup>) per gallon.  
 Do not thin.

**FILM THICKNESS:** Wet–4.0 mils  
 Dry–1.5 mils

**DRYING TIME:**

Dries to the touch in 30–60 minutes. Paint only when surface and air temperatures are 50–90°F (10–32°C). Recoat in 2–4 hours.

**APPLICATION:**

Stir paint thoroughly. Intermix all containers to ensure uniform color. Apply with a premium quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction.

**CLEAN-UP:**

Clean tools and hands with warm, soapy water.

**WASHING INSTRUCTIONS:**

Wait at least 7 days before washing with a mild detergent and soft sponge.

**PACKAGING:**

Gallons—4 Pack  
Quarts—4 Pack

**STORAGE AND DISPOSAL:**

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:**

**1-800-845-9061**

**TYPICAL ANALYSIS 16458**

<b>CAS NO.</b>	<b>INGREDIENTS</b>
7732-18-5	Water
Not Avail.	Acrylic Polymer
13463-67-7	Titanium Dioxide
66402-68-4	Ceramic Microspheres

**CAUTIONS:**

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

**FIRST AID:**

**EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than  
50 g/L VOC (0.5 lb./Gal VOS)**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.