



Duramax® Elastomeric Exterior Masonry & Stucco



Product Description

Valspar Duramax Elastomeric Masonry & Stucco Paint forms a weatherproof barrier against nature's harsh extremes. Stucco and masonry structures expand and contract in response to the weather and structural stresses. Unlike typical exterior paints, this coating fills and bridges hairline cracks, helping to prevent damaging water penetration. It passes Federal Specification TT-C-555B, sec. 3.3.3, withstanding 98 mph wind-driven rain. This premium quality coating protects your home like a flexible blanket...keeping your masonry & stucco safe and beautiful for years to come. It is available in white and can be tinted to many custom colors to make your home a showplace!

Features

- 100% Acrylic Latex Flat Finish
- Our Thickest High Build Coating
- Bridges Hairline Cracks
- Lifetime Flexibility, Won't Crack or Peel
- Superior Alkaline Resistance
- Gives Mold, Mildew & Algae Resistant Coating
- Withstands Wind-driven Rain
- Self Priming
- Superior Adhesion on Any Surface
- UV Resistant
- Apply as Low as 35°
- Soap & Water Clean-up

Recommended Uses

- Exterior masonry surfaces
- Cement
- Cinder block
- Stucco
- Concrete
- Brick
- Do not use on glazed brick, floors or steps

Colors and Base Information

| | oz./gal. |
|----------------|----------|
| Tintable White | 126 |

Reference Lowe's store Database for available colors.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon – 4 per carton
5-gallon pail

Typical Properties (197084)

Vehicle Type: Acrylic Resin

Sheen: 0–8 Units @ 60° angle

Solids by Volume: 43%

Solids by Weight: 57%

Weight per Gallon: 10.8 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 105–110 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 2 hour(s)

Recoat: 24 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 7 day(s)

Surface Coverage:

Smooth Surface: 130 sq. ft./gal.

Rough: 90 sq. ft./gal.

At: 16 mil Wet, 7 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Apply paint to clean, sound surfaces. Large cracks, crumbling areas or water damage may need professional repair. New concrete or stucco must cure a month before applying a finish. **Cleaning the Surface:** Old or existing surfaces; remove dirt, grease, mildew, algae, efflorescence and loose, peeling coating. Pressure washer and masonry and stucco cleaner will ensure a clean, chalk and dirt free surface. Follow all label instructions and rinse well. **Caution: Improper power washer use may cause damage to stucco.** **Filling in Cracks and Patching:** Hairline cracks (1/16" or less) can be covered with this product. Cracks larger than 1/16" must be cleaned to remove all loose stucco or masonry. For stucco, fill gaps with exterior stucco texture finish, following label instructions. For masonry gaps, fill with concrete patch. Note: Large areas of crumbling masonry indicate a serious problem; consult a professional contractor. **Priming:** Priming is not required on masonry surfaces in sound or good condition (cured, no efflorescence, etc.). For new masonry and stucco, mildly chalking surface or if in poor condition, prime with Valspar Exterior Latex Primer. If overall surface is in good condition, spot prime as needed. Coarse textured surfaces require a block filler. **Caulking:** Caulk all joints, seams and cracks around windows, doors and trim to eliminate sources of moisture entry. **Clean Mildew from the Surface:** To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin or eyes.

Application and Clean-up

Paint only when surface and air temperatures are 35–90 °F (2–32 °C). Use a paint paddle to stir paint up from the bottom of the can. Intermix containers of the same color. Apply this product heavily to achieve best weatherproofing characteristics. **Roller:** Preferred method of application. For best results, use a quality 1" to 1-1/4" nap synthetic roller cover. Always roll with a fully loaded wet roller – never dry roll. Do not stretch this coating. Be sure all low spots and gaps are covered. It is normal for painted surfaces to show roller marks. **Airless Sprayer:** Use 1-2 gallon per minute capacity pump at 2500 psi minimum with a 0.025 tip. Adjust pressures to suit your needs. Always follow spray application by back-rolling with a wet applicator. This will ensure that the paint is worked into the surface. Thin with water for spray application (no more than 8 oz. per gallon), if needed. **Brush:** Not recommended. Use only for small touch-ups. Clean up with warm, soapy water.

Cautions (197084)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.