



## Ultra Premium Interior/Exterior Latex High Gloss Enamel Series



### Product Description

Valspar® Ultra Premium High Gloss Enamel is ideal for shutters or trim. It's guaranteed to last a lifetime inside or outside your home. Just one coat provides our most durable and scrubbable enamel that gives a mildew resistant finish.

### Features

- Long Lasting Durability
- Thick, One Coat Coverage
- Most Durable & Scrubbable
- Easy Clean-Up
- Low Odor
- Gives Mildew Resistant Finish

### Recommended Uses

- Wood Siding & Trim
- Primed Metal

### Colors and Base Information

	oz./gal.
White	128
Base 1	126
Base 2	124
Base 4	116

Reference Lowe's store database for available colors.

### Shipping and Packaging

**Freight Classification:** Paint or Paint Related Material. Protect from freezing.

**Packaging:** Quart & Gallon – 4 per carton  
5-gallon pail

### Typical Properties (222140 White)

**Vehicle Type:** Acrylic Resin

**Sheen:** 70+ Units @ 60° angle

**Solids by Volume:** 34%

**Solids by Weight:** 46%

**Weight per Gallon:** 10.2 lbs./gal.

**VOC:** Less than 150 g/L

**Viscosity:** 86 – 92 Krebs Units

**Dry Time:** 77°F @ 50% Relative Humidity

**To the touch:** 1 hour

**Recoat:** Overnight

**Surface Coverage:**

400 sq. ft./gal. (27.9 - 37.2 m<sup>2</sup>) depending on surface porosity.

**At:** 4 mil Wet, 1.5 mil Dry

### Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

### Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all mildew, dirt, dust, rust and grease. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin or eyes.

PDS 0160

## Priming

**Previously Painted Surfaces (including painted metal siding):** Scrape loose and peeling paint, sand, then prime. Wire brush chalking areas and clean with TSP (or equivalent) and water. Dull glossy surfaces with gloss remover or sand paper. Countersink nails and apply a rust inhibitive metal primer on exposed nail heads.

**Bare Wood:** Remove sap and clean knotty areas. Seal these areas by spot priming with an oil-based primer.

**Wallboard, Tape Joints and Plaster:** Sand smooth, remove dust with damp cloth or sponge, then prime.

**Masonry:** Brush loose sand, dust and other material from the surface.

**Metal:** May be used to prime weathered, non-rusted galvanized gutters and downspouts. New galvanized surfaces should be primed with a galvanized metal primer, or washed with a mild muriatic acid solution, or allowed to weather for six months before painting. All iron and steel surfaces should be primed with a rust inhibitive metal primer.

## Application and Clean-up

Stir paint thoroughly before and during use. Intermix all containers to ensure uniform color. Paint only when surface and air temperatures are 50 – 90°F (10 – 32°C) during application and drying time. Thin only for spraying with up to 8 oz. of water per gallon of paint. Apply with a premium quality roller, polyester brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of paint uniformly, working well into the surface. Clean tools and hands with warm, soapy water.

## Cautions (222140 White)

**WARNING:** May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after use.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than 150 g/L VOC**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

PDS 0160