

PRODUCT INFORMATION

1191 Wheeling Road, Wheeling, IL 60090
 Phone: 847-541-9000 Fax: 847-541-7549



183 Medallion Exterior Oil Primer

PRODUCT: 183 White

DESCRIPTION:

Medallion® Exterior Oil Primer

FEATURES:

Medallion Exterior Oil Primer is the perfect base coat for all oil and latex house paints, adding long-lasting protection to your home as it resists weather-related problems such as peeling and blistering. Gives mildew resistant coating that helps promote topcoat adhesion as it seals and primes exterior surfaces.

WHERE TO USE:

Use on properly prepared exterior surfaces such as hardboard siding and trim, bare wood and previously painted, unprimed wood siding and trim, bare redwood, cedar, cypress, fir or gummy pine.

SURFACE PREPARATION:

General: Clean and dry surface thoroughly, removing all dirt, dust, rust and grease.

Bare Wood: Prime the entire surface with this product.

Previously Painted Surfaces: Scrape, sand, then prime. Wire brush badly chalking areas and wash with TSP and water. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails, fill with putty. Apply a rust inhibitive metal primer on exposed nails. Caulk all cracks and joints.

Metal: Remove rust and apply a rust inhibitive metal primer.

Hardboard Siding: Remove any wax from bleed-through areas by wiping with a mineral spirits soaked cloth, turning the cloth often.

TYPICAL PRODUCT PROPERTIES:

VEHICLE TYPE: Alkyd Resins
 SOLIDS: 67% WT. 44% VOL.
 VOC: 350 g/l max
 WT/GAL: 10.7 lbs.
 VISCOSITY: 71-77 KU
 FLASHPOINT: 52 F
 60° GLOSS: 3-9 Units

COVERAGE/THINNING:

One gallon covers up to 400 sq. ft. (37.2 m²) depending on surface porosity. Do not thin.

FILM THICKNESS:

4.0 mil Wet 2.2 mil Dry

DRY TIMES:

Apply only when air and surface temperatures are between 50-90°F (10-32°C). Dries to the touch in 6-8 hours. Dry overnight before applying topcoat. Finish coat should be applied within 30 days following primer application.

183 Medallion Exterior Oil Primer

APPLICATION:

Stir thoroughly before and during use. Apply with a premium quality "one coat" roller, natural or polyester bristle brush or airless sprayer. If applying by spray, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer evenly, working well into the surface.

CLEAN-UP:

Clean-up with mineral spirits.

PACKAGING:

Gallons & Quarts: 4 Pack

STORAGE AND DISPOSAL:

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. **Danger:** Rags, steel wool, sanding dust or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, sanding dust or waste in a sealed, water-filled metal container.

Product Information Hotline:

1-800-845-9061

DO NOT TAKE INTERNALLY.

KEEP OUT OF THE REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

**This product contains less than
350 g/L VOC (2.9 lb./Gal VOS)**

TYPICAL ANALYSIS:

CAS NO.	INGREDIENTS
37244-96-5	Nepheline Syenite
66070-60-8	Alkyd Resin
1317-65-3	Calcium Carbonate
13463-67-7	Titanium Dioxide
8052-41-3	Exempt Mineral Spirits
1897-45-6	Chlorothalonil
14808-60-7	Crystalline Silica

CAUTIONS:

CONTAINS PETROLEUM DISTILLATE AND CRYSTALLINE SILICA

May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **USE ONLY WITH ADEQUATE VENTILATION.** Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Do not induce vomiting. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.