

PRODUCT INFORMATION

1191 Wheeling Road, Wheeling, IL 60090
 Phone: 847-541-9000 Fax: 847-541-7549



27-2400 Series Valspar Medallion Interior Semi-Gloss Wall & Trim

PRODUCT: 2400 Series

DESCRIPTION:

Valspar Medallion 100% Acrylic Interior Semi-Gloss Latex Wall & Trim

FEATURES:

This durable wall paint protects with a 100% acrylic coating for a flawless finish and enduring beauty. The tough semi-gloss sheen offers a scrubbable, stain resistant coating perfect for high traffic areas. Dries quickly and cleans up easily with soap and water.

WHERE TO USE:

Properly prepared interior wall and ceiling surfaces including previously painted and primed plaster, brick, drywall, cement, wood, metal and wallpaper.

SURFACE PREPARATION:

Clean and dry the surface thoroughly, removing all dirt, dust, rust, grease and wax. Scrape off loose paint and wallpaper. Remove glue, shellac and sizing. Patch cracks and prime. Dull glossy surfaces with gloss remover or sandpaper. Remove chalky residue and prime unpainted plaster and wallboard with latex wall primer. New wood surfaces should be sanded smooth and primed with latex wood trim primer or latex wall primer. If painting over wallpaper, test pattern for bleeding. If bleeding occurs, remove the paper or prime with oil-based stain block or latex stain killer primers.

Care & Washing: Allow fresh paint to cure at least 7 days before washing. Always use a mild detergent and soft sponge when cleaning the surface. Stubborn stains may require the use of an ammoniated household cleaner for complete removal. Do not use cleaners containing abrasives or abrasive scouring pads to clean the painted surface.

TYPICAL PRODUCT PROPERTIES:

2400 White

VEHICLE TYPE: Acrylic Resin
 SOLIDS: 48% WT. 36% VOL.
 VOC: 250 g/L max
 WT/GAL: 10.3 lbs.
 VISCOSITY: 94-100 KU
 FLASHPOINT: N.A.
 60° GLOSS: 30-40

COVERAGE: 400 Sq. Ft. per gallon depending on porosity. With some colors or drastic color changes, more than one coat may be necessary to achieve a uniform finish.

FILM THICKNESS: 4.0 Wet 1.4 Dry
DRY TIMES: Dries to touch in 30 minutes, 4 hours before recoating, longer in high humidity or cool temperatures. Paint only when surface and air temperatures are 50-90°F during application and drying time.

APPLICATION:

Stir paint thoroughly before and occasionally during use. Use a premium quality roller or polyester brush or airless sprayer following manufacturers directions. Paint the ceiling first, then the walls, rolling from dry into wet areas using firm, crisscross strokes.

THINNING/CLEAN UP:

Thin only for spray application with up to 8 oz water per gallon of paint. Clean up with warm water.

PACKAGING:

Quarts & Gallons	4 Pack
5 gallon pails	Each

STORAGE AND DISPOSAL:

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Product Information Hotline:

1-800-845-9061

TYPICAL ANALYSIS (2400 White)

C.A.S. NO.	INGREDIENTS
7732-18-5	WATER
13463-67-7	TITANIUM DIOXIDE
Not Avail.	ACRYLIC EMULSION
57-55-1	PROPYLENE GLYCOL
14808-60-7	CRYSTALLINE SILICA

CAUTIONS:

CONTAINS CRYSTALLINE SILICA.

May cause eye and skin irritation. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after the application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**
Delayed effect from long term exposure: Contains crystalline silica which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-800-228-5635

This product contains less than 250 g/L VOC (2.1 lb./Gal VOS)

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.