



Contractor Finishes 2000 Interior Latex Eggshell Series



Product Description

A premium quality, high hiding eggshell finish designed for interior walls and ceilings. Formulated for the professional; it can be sprayed & rolled with low spatter. The eggshell finish provides excellent touch-up properties.

Features

- High Hiding
- Superior Touch-up
- Washable
- Low Odor & VOC
- Low Spatter
- Easy Application
- Soap & Water Clean-up

Recommended Uses

- Drywall
- Plaster
- Masonry
- Primed Wood or Metal
- Previously Painted Surfaces

Colors and Base Information

	oz./gal.
Ready Mix*	128
Pastel Tint Base	124
Medium Tint Base	120
Neutral Tint Base	116

Reference Lowe's store Database for available colors.

*Dover White, Swiss Coffee, Antique White, High Hide White

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon – 4 per carton
5-gallon pail

Typical Properties (30919 High Hide White)

Vehicle Type: Vinyl Acrylic

Sheen: 10 – 20 Units @ 85° angle

Solids by Volume: 29.6%

Weight per Gallon: 10.6 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 90 – 100 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 1 hour

Recoat: 4 hours

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 30 days

Surface Coverage:

Smooth Surface: 350 – 450 sq. ft./gal.

Rough: 250 – 350 sq. ft./gal.

At: 4 mil Wet, 1.2 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean the surface thoroughly to remove surface contamination, mildew, stains, and rust with an appropriate cleaner. Scrape off any loose or peeling paint. Spot prime when needed. Dull glossy surfaces with light sanding.

Priming

Drywall: Remove sanding dust and prime with Valspar Drywall Primer.

Block: Remove any loose material or efflorescence and prime with Block Filler.

Masonry, Concrete: Remove any loose material or efflorescence and prime with Valspar Latex Multi-Purpose Primer.

New Wood: Sand smooth, clean and prime with Latex Enamel Undercoat.

Aluminum: None.

Steel: Remove any loose or flaking rust by hand sanding or power tool cleaning. Prime with Alkyd Metal Primer.

Stained Areas: Valspar® Bonding Primer

Application and Clean-up

Stir thoroughly and intermix multiple containers. Apply product at temperatures ranging from 50 – 90°F. Apply by brush, roller or spray application. Thinning is not recommended, but if needed for spray application, use up to 8 ounces of water per gallon. **Brush** – Premium quality nylon/polyester blend. **Roller** – 3/8" to 3/4" premium quality synthetic cover. **Airless Spray** – 0.017 – 0.019 Tip @ 2000 PSI. Note: These recommendations are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding. Clean-up tools, spills and spatters with warm, soapy water.

Cautions (30919 High Hide White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.