

PDS #615
PRODUCT INFORMATION

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



65735 Series Valspar Ultra Premium Ltx Porch & Floor Enamel

PRODUCT: 65735 Series

DESCRIPTION:

Valspar Ultra Premium Latex Porch & Floor Enamel

FEATURES:

Interior/Exterior Latex Porch & Floor Enamel is a non-glare, very low sheen acrylic coating which gives floors tough, long-lasting protection. The latex formula is ideal for indoor applications where low odor and fast dry are important. Durable and weather resistant, this enamel lasts for years in exterior applications. Easy water clean up.

WHERE TO USE:

Properly prepared concrete, wood, porches, basement floors, stairs, breezeways, primed metal, indoor and outdoor floors. **Not for use on exterior wood decks, garage floors or other automobile parking areas.**

SURFACE PREPARATION:

The surface must be clean, dry and free of all loose, peeling or cracking paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute), scouring powder, wax remover or diluted ammonia. Wire brush or scrape chipped or peeling paint. Rough or repaired wood surfaces should be sanded smooth. Prime bare, new wood with an enamel undercoater. Prime badly worn spots on old wood with a thinned first coat of Latex Porch & Floor Enamel. All rust must be removed from metal prior to painting. Prime all iron and steel with a rust inhibiting metal primer. Remove gloss from previously painted surfaces with gloss remover or by sanding. For new concrete, allow surface to cure at least 60 days before painting. Then, acid etch with muriatic acid (See etching instructions and read all cautions on etching packages). Unpainted or smooth-worn concrete should also be etched. After acid etching, apply two coats of Latex Porch & Floor Enamel - the first coat thinned with 1 pint water per gallon of paint.

Etching Instructions: New, unpainted or smooth-worn concrete must be etched with a muriatic acid solution for proper penetration and adhesion. Before preparing acid solution, READ ALL CAUTIONS AND WARNINGS on acid packaging. Wear appropriate protective clothing, goggles and rubber gloves when handling acid. Mix 1 quart of muriatic acid and 1 gallon of water. Flush floor with acid solution. DO NOT BREATHE VAPORS and make certain there is good ventilation. After 30 minutes, or when acid solution stops bubbling, rinse with water while scrubbing floor with stiff broom to remove all powdery residue. Allow to dry.

TYPICAL PRODUCT PROPERTIES: (65735)

VEHICLE TYPE: Acrylic Resin
SOLIDS: 39% WT. 29% VOL.
VOC: 100 g/l max
WT/GAL: 9.8 lbs.
VISCOSITY: 87-93 KU
FLASHPOINT: N/A
60° GLOSS: 7-13 Units

COVERAGE: One gallon covers up to 400 sq. ft. (37.2m²) depending upon surface porosity. For surfaces that do require two coats, such as new concrete or badly worn areas, thin first coat only with 1 pint water per gallon of paint; apply second coat as normal.

FILM THICKNESS: 4.0 mil Wet
1.2 mil Dry

DRY TIMES: Dries to the touch in about 1 hour, longer in high humidity or cool temperatures. Do not apply when surface and air temperatures are below 50°F (10°C). Allow 4-6 hours before light foot traffic and 24 hours for normal use. Allow overnight drying before recoating.

APPLICATION:

Stir paint thoroughly before and during use. If using more than one can of the same color, intermix to maintain color consistency. To increase traction on stairs and other areas where accidental slips may occur, add Valspar® Anti-Skid Additive or one cup of clean, dry sand when applying the finishing coat. Stir frequently during application to avoid settling. Use a premium quality roller, polyester brush, pad applicator or airless sprayer. **DO NOT USE SAND IF SPRAYING.** Apply liberally over the full length of the surface to avoid lap marks. If applied by airless sprayer, back roll to ensure proper penetration. Finish with long, even strokes in one direction.

Care & Washing Instructions: Do not allow water to pond or puddle on new painted surfaces. Allow to cure 7 days before washing. Always use a mild detergent and soft sponge when cleaning the surface. Stubborn stains may require the use of an ammoniated household cleaner. Do not use cleaners containing abrasives or abrasive scouring pads to clean the surface.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

THINNING/CLEAN UP:

Thinning is generally not recommended. Clean tools and hands with warm, soapy water.

PACKAGING:

Gallons & Quarts 4 Pack

Product Information Hotline: 1-888-313-5569

TYPICAL ANALYSIS (65735)

C.A.S. NO.	INGREDIENTS
7732-18-5	WATER
25035-69-2	ACRYLIC COPOLYMER
UNKNOWN	NEPHELINE SYENITE
13463-67-7	TITANIUM DIOXIDE
57-55-6	PROPYLENE GLYCOL
14808-60-7	CRYSTALLINE SILICA
1333-86-4	CARBON BLACK

CAUTIONS:

CONTAINS CRYSTALLINE SILICA.

May cause eye and skin irritation. Avoid breathing vapors or spray mist. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **FIRST AID:** **EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.** **Delayed effect from long-term exposure:** Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to sanding dust.

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732
This product contains less than 100 g/L VOC (0.8 lb./Gal VOS)

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. **PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.