

**PDS #5187**  
**PRODUCT INFORMATION**

valspar

1191 Wheeling Road, Wheeling, IL 60090  
Phone: 847-541-9000 Fax: 847-541-7549



**95951 Valspar Ultra Premium Sand Texture Paint**

**PRODUCT: 95951**

**DESCRIPTION:**

Valspar Ultra Premium Interior Latex Acrylic Sand Texture Paint

**FEATURES:**

Beautify your interior ceilings and walls with American Tradition Sand Texture Paint. This premium quality paint provides a subtle sandpaper-like texture to help hide minor surface imperfections.

**WHERE TO USE:**

Use on properly prepared interior wall and ceiling surfaces, including previously painted and properly primed plaster, drywall, wood, metal, cement, brick and masonry. **DO NOT USE OVER WALLPAPER.**

**SURFACE PREPARATION:**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces. Remove chalky residue and prime new wallboard with latex wall primer. New plaster and masonry must cure 30 days before priming. Prime bare wood with an acrylic enamel undercoater. Prime ferrous metal with a rust inhibiting oil metal primer. For other metals, use appropriate metal primer. Water stained ceilings or other stained areas must be primed with a latex or oil-base stain block primer to prevent bleed-through.

Note: Oil-based primers dry to a hard, slippery surface and must be roughened by sanding to increase texture paint adhesion.

---

**TYPICAL PRODUCT PROPERTIES:**  
**(95951 Sand Texture)**

VEHICLE TYPE: Vinyl Acrylic  
SOLIDS: 59% WT. 38% VOL.  
VOC: 100 g/l max  
WT/GAL: 12.9 lbs.  
VISCOSITY: 141+ KU  
FLASHPOINT: N/A  
60° GLOSS: N/A

**COVERAGE/THINNING:**

One gallon covers approximately 75-125 sq. ft. (6.9-11.6 m<sup>2</sup>) depending upon texture pattern and surface porosity. A heavier stipple requires more paint. Thin sparingly only if paint becomes too thick to apply.

**FILM THICKNESS:** 32 mil Wet  
12 mil Dry

**DRY TIMES:**

Paint only when surface and air temperatures are 50-90°F (10-32°C). Dries hard overnight and cures fully in one week. Allow to dry 48 hours before recoating.

**APPLICATION:**

Stir paint thoroughly before and during use. Intermix all containers of the same color. If creating a pattern, experiment on heavy cardboard or plywood. Apply a generous coat of texture paint to the surface using a stiff brush, putty knife or trowel. If a pattern is desired, create it first while the texture paint is wet. Work in 3-foot areas blending patterned areas together. May be recoated with interior latex satin or semi-gloss paint for hallways or other surfaces requiring occasional washings to remove household soils.

**CLEAN UP:**

Clean up with warm, soapy water.

**PACKAGING:**

Gallons                    4 Pack  
2-Gallon Pail        Each

**STORAGE AND DISPOSAL:**

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:  
1-888-313-5569**

**TYPICAL ANALYSIS (95951 Sand Texture)**

<b>C.A.S. NO.</b>	<b>INGREDIENTS</b>
7732-18-5	Water
1317-65-3	Calcium Carbonate
7631-86-9	Silica
93763-70-3	Amorphous Silica
25067-01-0	Vinyl Acrylic Copolymer
13463-67-7	Titanium Dioxide
14808-60-7	Crystalline Silica

**CAUTIONS:**

**CONTAINS CRYSTALLINE SILICA**

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. Warning: This product contains a chemical known to the state of California to cause cancer.

**FIRST AID:**

**EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.** **Delayed effect from long-term exposure:** Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**  
**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**  
**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**  
**This product contains less than  
100 g/L VOC (0.8 lb./Gal VOS)**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.